

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2014

Revised On 10/09/2014

## 1 Identification of the substance and manufacturer

**Trade name:** GOOD GRIP CLEAR

**Product code:** 0000160081

**Product category:** PC9a Paints and coatings.

**Manufacturer/Supplier:** Seymour of Sycamore  
917 Crosby Avenue  
Sycamore, IL 60178  
Phone: 815-895-9101 www.seymourpaint.com

**Emergency telephone number:** CHEMTEL 1-800-255-3924, 813-248-0585 \*if located outside the U.S.\*



## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word

### Hazard statements

Danger

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

### Precautionary statements

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

### Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

|           |                        |        |
|-----------|------------------------|--------|
| 67-64-1   | Acetone                | 38.37% |
| 74-98-6   | propane                | 13.87% |
| 1330-20-7 | xylene (mix)           | 9.36%  |
| 106-97-8  | n-butane               | 8.15%  |
| 108-10-1  | methyl isobutyl ketone | 6.22%  |
| 100-41-4  | ethyl benzene          | 2.34%  |
| 108-65-6  | PM acetate             | 1.91%  |
| 9002-88-4 | Polyethylene           | 1.86%  |
| 1317-65-3 | Calcium Carbonate      | 1.58%  |

## 4 First-aid measures

### General information:

Symptoms of poisoning may occur even after several hours. Medical observation for at least 48 hours after the accident is recommended.

### After inhalation:

Supply fresh air. If necessary, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

### After skin contact:

Supply fresh air; consult doctor in case of complaints.

### After eye contact:

Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

### After swallowing:

Rinse out mouth and then drink plenty of water.

(Contd. on page 2)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2014

Revised On 10/09/2014

Trade name: GOOD GRIP CLEAR

(Contd. of page 1)

**Most important symptoms and effects:**

Rinse mouth with water. Do not induce vomiting.

**Indication of any immediate medical attention needed:**

Dizziness

No further relevant information available.

**5 Fire-fighting measures****Extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.**Special hazards:**

Can form explosive gas-air mixtures.

**Protective equipment for firefighters:**

A respiratory protective device may be necessary.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures:**Wear protective equipment. Keep unprotected persons away.  
Use respiratory protective device against the effects of fumes/dust/aerosol.**Methods and material for containment and cleaning up:**Ensure adequate ventilation.  
Dispose contaminated material as waste according to section 13.**7 Handling and storage****Precautions for safe handling**

Use only in well ventilated areas.

**Storage requirements:**

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm  |
| REL (USA) | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm  |
| TLV (USA) | Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm<br>Long-term value: (1188) NIC-594 mg/m <sup>3</sup> , (500) NIC-250 ppm<br>BEI |

**74-98-6 propane**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| TLV (USA) | refer to Appendix F                                |

**1330-20-7 xylene (mix)**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm   |
| REL (USA) | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm        |
| TLV (USA) | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm<br>BEI |

**106-97-8 n-butane**

|           |   |
|-----------|---|
| REL (USA) | Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm   |
| TLV (USA) | Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm |

**108-10-1 methyl isobutyl ketone**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 410 mg/m <sup>3</sup> , 100 ppm  |
| REL (USA) | Short-term value: 300 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 205 mg/m <sup>3</sup> , 50 ppm       |
| TLV (USA) | Short-term value: 307 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 82 mg/m <sup>3</sup> , 20 ppm<br>BEI |

**100-41-4 ethyl benzene**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| REL (USA) | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV (USA) | Long-term value: 87 mg/m <sup>3</sup> , 20 ppm<br>BEI   |

**108-65-6 PM acetate**

|            |                         |
|------------|-------------------------|
| WEEL (USA) | Long-term value: 50 ppm |
|------------|-------------------------|

**Ingredients with biological limit values:****67-64-1 Acetone**

|           |  |
|-----------|--|
| BEI (USA) | 50 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Acetone (nonspecific) |
|-----------|--|

(Contd. on page 3)

US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2014

Revised On 10/09/2014

Trade name: GOOD GRIP CLEAR

(Contd. of page 2)

**1330-20-7 xylene (mix)**

BEI (USA) 1.5 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

**108-10-1 methyl isobutyl ketone**

BEI (USA) 1 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: MIBK

**100-41-4 ethyl benzene**

BEI (USA) 0.7 g/g creatinine  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
 Medium: end-exhaled air  
 Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

**Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands after use.  
 Avoid contact with the eyes and skin.

**Breathing equipment:**

Do not eat or drink while working.  
 A respirator is generally not necessary when using this product outdoors or in large open areas.  
 In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Protective gloves. The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties**

**Appearance:** Aerosol.  
**Odor:** Aromatic  
**Odor threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/Melting range** Undetermined.  
**Boiling point:** -44 °C (-47 °F)  
**Flash point:** -19 °C (-2 °F)  
**Flammability (solid, gas):** Extremely flammable.  
**Decomposition temperature:** Not determined.  
**Auto igniting:** Product is not self-igniting.  
**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
**Lower Explosion Limit:** 1.7 Vol %  
**Upper Explosion Limit:** 10.9 Vol %  
**Vapor pressure:** Not determined.  
**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)  
**Vapour density** Not determined.  
**Evaporation rate** Not applicable.  
**Partition coefficient: n-octonal/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.  
**VOC content:** 519.6 g/l / 4.34 lb/gl  
**VOC content (less exempt solvents):** 42.8 %  
**MIR Value:** 1.47  
**Solids content:** 18.9 %

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

**11 Toxicological information****LD/LC50 values that are relevant for classification:****1330-20-7 xylene (mix)**

|      |      |                  |
|------|------|------------------|
| Oral | LD50 | 8700 mg/kg (rat) |
|------|------|------------------|

(Contd. on page 4)  
US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2014

Revised On 10/09/2014

**Trade name: GOOD GRIP CLEAR**

(Contd. of page 3)

|  |          |                     |
|--|----------|---------------------|
| Dermal                                 | LD50     | 2000 mg/kg (rbt)    |
| Inhalative                             | LC50/4 h | 6350 mg/l (rat)     |
| <b>106-97-8 n-butane</b>               |          |                     |
| Inhalative                             | LC50/4 h | 658 mg/l (rat)      |
| <b>108-10-1 methyl isobutyl ketone</b> |          |                     |
| Oral                                   | LD50     | 2100 mg/kg (rat)    |
| Dermal                                 | LD50     | 16000 mg/kg (rab)   |
| Inhalative                             | LC50/4 h | 8.3-16.6 mg/l (rat) |
| <b>100-41-4 ethyl benzene</b>          |          |                     |
| Oral                                   | LD50     | 3500 mg/kg (rat)    |
| Dermal                                 | LD50     | 17800 mg/kg (rbt)   |
| <b>108-65-6 PM acetate</b>             |          |                     |
| Oral                                   | LD50     | 8500 mg/kg (rat)    |
| Inhalative                             | LC50/4 h | 35.7 mg/l (rat)     |

**Information on toxicological effects:** No data available.  
**Sensitization:** No sensitizing effects known.

**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

|           |                        |    |
|-----------|------------------------|----|
| 1330-20-7 | xylene (mix)           | 3  |
| 108-10-1  | methyl isobutyl ketone | 2B |
| 100-41-4  | ethyl benzene          | 2B |

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

**UN-Number** UN1950  
**ADR** 1950 AEROSOLS  
**Transport hazard class(es):**  
**Class** 2.1  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Packaging Group:** --  
**UN "Model Regulation":** UN1950, Aerosols, 2.1

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

|           |                        |
|-----------|------------------------|
| 1330-20-7 | xylene (mix)           |
| 108-10-1  | methyl isobutyl ketone |
| 100-41-4  | ethyl benzene          |

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

|          |                        |
|----------|------------------------|
| 108-10-1 | methyl isobutyl ketone |
| 100-41-4 | ethyl benzene          |

**Canadian WHMIS:** D2A**EPA:**

|           |                        |   |
|-----------|------------------------|---|
| 67-64-1   | Acetone                | I |
| 1330-20-7 | xylene (mix)           | I |
| 108-10-1  | methyl isobutyl ketone | I |

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2014

Revised On 10/09/2014

**Trade name: GOOD GRIP CLEAR**

(Contd. of page 4)

100-41-4 ethyl benzene

D

## 16 Other information

**Contact:** Regulatory Affairs

US4